



KA-10/1PACK

Order No.: 0253120

Price upon request

PRODUCTINFOS

Wireless 16-channel PLL audio transmission system for cameras

- Consisting of a portable audio transmitter and receiver
- Carrier frequency range: 863-865 MHz
- Transmitter and receiver with rechargeable lithium-ion batteries for reducing the weight and to ensure long operating times
- Transmitter can also be used for transmitting line signals (adjustment via recessed gain control)
- Receiver with 3-step PAD switch (0dB/-10 dB/-20 dB) for perfect level matching to the audio input of the camera
- Transmitter and receiver are fitted with a robust metal fixing clip
- Operating time: approx. 12 hours
- Supplied with lavalier microphone in skin design with windshield and tie clip, attachment clip for camera mounting, trim key, dual charging slot with plug-in switch-mode power supply, connection cable with 3.5 mm plug to 3.5 mm plug, connection cable with 3.5 mm plug to XLR plug

Licence-free in the EU.

Supplied w/o camera.

TECHNICAL SPECIFICATIONS

KA-10/1PACK

General information

Description 16-channel PLL audio transmission system

Carrier frequency range 863-865 MHz

Audio frequency range 40-18,000 Hz

Channels 16

THD < 1%

Admiss. ambient temp. 0-40 °C

Specifications transmitter

Transmitting power < 10 mW

Operating range approx. 60 m

Power supply transmitter 3.7 V rech. lithium-ion battery

Width transmitter 55 mm

Height transmitter 100 mm

Depth transmitter 18 mm

Weight transmitter 80 g

Specifications receiver

Audio signal receiver 300 mV/7 kΩ (jack)

Power supply receiver 3.7 V rech. lithium-ion battery

Width receiver 55 mm

Height receiver 100 mm

Depth receiver 18 mm

Weight receiver 82 g

Connections receiver 1 x 3.5 mm jack (transmitter)

1 x 3.5 mm jack (receiver)