



PAB-416/SW

Order No.: 0131870

Price upon request

PRODUCTINFOS

This particularly attractive and efficient series of PA speaker systems

is clearly designed for effective fixed installations, whether in restaurants and bars, hotels, for background PA applications at sport facilities, PA applications in adjoining rooms at discotheques or at conferences: these PAB speaker systems offer a perfect price-performance ratio and a high quality.

Pairs of high-quality PA speakers, 20 W, 16 Ω

- 2-way speaker systems in an ABS cabinet which is both functional and at the same time of an attractive appearance
- Polypropylene bass speaker and dome tweeter with horn front attachment (waveguide)
- High-quality crossover networks with a perfect long-term stability, e.g. due to consistently applying film capacitors
- Very well-balanced and clear sound which also convinces with the genuine reproduction of voices and demanding music and at the same time appears to be very unobtrusive at moderate levels
- Supplied with wall bracket

Due to the availability of the PAB-416/... speaker systems in 16 Ω , too, up to 8 speaker systems can be driven at one 2-channel standard amplifier with 4 Ω stability by means of basic parallel connection.

TECHNICAL SPECIFICATIONS

PAB-416/SW

Active/passive	passive
Total power rating	30 W
Power rating (RMS)	20 W
Impedance	16 Ω
Frequency range	80-22,000 Hz
System	2-way
Bass speaker	polypropylene bass speaker
Tweeter	dome tweeter
Number of speakers	2
Sensitivity	87 dB/W/m
Max. rated SPL	100 dB
Housing material	ABS plastic
Colour	black
Mounting device	2 x thread M6
Admiss. ambient temp.	0-40 °C
Dimensions	150 x 240 x 140 mm
Width	150 mm
Height	240 mm
Depth	140 mm
Weight	1.8 kg
Inputs	speaker screw terminal
Packing dimensions (W x H x L)	0.18 x 0.26 x 0.38 m
Gross weight	3.71 kg
Net weight	3.368 kg