



## PAB-416/WS

Order No.: 0131880

**Price upon request**

### PRODUCTINFOS

#### **This particularly attractive and efficient series of PA speaker systems**

is clearly designed for effective fixed installations, whether in restaurants and bars, hotels, for background PA applications at sport facilities, PA applications in adjoining rooms at discotheques or at conferences: these PAB speaker systems offer a perfect price-performance ratio and a high quality.

#### **Pairs of high-quality PA speakers, 20 W, 16 $\Omega$**

- 2-way speaker systems in an ABS cabinet which is both functional and at the same time of an attractive appearance
- Polypropylene bass speaker and dome tweeter with horn front attachment (waveguide)
- High-quality crossover networks with a perfect long-term stability, e.g. due to consistently applying film capacitors
- Very well-balanced and clear sound which also convinces with the genuine reproduction of voices and demanding music and at the same time appears to be very unobtrusive at moderate levels
- Supplied with wall bracket

Due to the availability of the PAB-416/... speaker systems in 16  $\Omega$ , too, up to 8 speaker systems can be driven at one 2-channel standard amplifier with 4  $\Omega$  stability by means of basic parallel connection.

## TECHNICAL SPECIFICATIONS

### PAB-416/WS

Active/passive	passive
Total power rating	30 W
Power rating (RMS)	20 W
Impedance	16 $\Omega$
Frequency range	80-22,000 Hz
System	2-way
Bass speaker	polypropylene bass speaker
Tweeter	dome tweeter
Number of speakers	2
Sensitivity	87 dB/W/m
Max. rated SPL	100 dB
Housing material	ABS plastic
Colour	white
Mounting device	2 x thread M6
Admiss. ambient temp.	0-40 °C
Dimensions	150 x 240 x 140 mm
Width	150 mm
Height	240 mm
Depth	140 mm
Weight	1.8 kg
Inputs	speaker screw terminal
Packing dimensions (W x H x L)	0.18 x 0.26 x 0.38 m
Gross weight	3.71 kg
Net weight	3.368 kg