



SPE-15F/WS

Order No.: 0162840

Price upon request

PRODUCTINFOS

Pair of weatherproof flush-mount PA speakers, 15 W,

with UV-stabilised plastic housing, super slimline design.

Versatile use for PA, car hi-fi, terrace, boat, swimming pool areas.

- Weatherproof polypropylene spaker cone
- Tested according to ASTM B117 (400 h salt spray test)
- Low stray magnetic field
- Supplied with stainless mounting accessories and connection cable

TECHNICAL SPECIFICATIONS

SPE-15F/WS

Impedance (Z)	4 Ω
Frequency range	80-16,000 Hz
Power rating (RMS)	15 W

SPE-15F/WS

Peak music power output (MAX)	30 W
Sensitivity	86 dB/W/m
Magnet weight	83 g
Mounting cutout	Ø 111 mm
Mounting depth	25 mm
Dimensions	Ø 150 mm x 45 mm
Outside diameter	Ø 150 mm
Width	Ø 150 mm
Depth	45 mm
Protective class	IP65
Admiss. ambient temp.	0-40 °C
Weight	270 g
Packing unit	2
Type of speaker	130
Packing dimensions (W x H x L)	0.16 x 0.06 x 0.315 m
Gross weight	0.83 kg
Net weight	0.645 kg