



SPE-284/WS

Order No.: 0105520

Price upon request

PRODUCTINFOS

Pair of weatherproof PA ceiling speakers, heat-resistant up to 100 °C.

For applications in saunas and swimming pool areas.

- 2-way system with dome tweeter
- Excellent sound
- White plastic housing
- Weatherproof speaker cone
- Tested according to ASTM B117 (400 h salt spray test)
- For a ceiling thickness from 2 to 25 mm
- Spring-loaded speaker terminals

TECHNICAL SPECIFICATIONS

SPE-284/WS

Impedance (Z)	4 Ω
Frequency range	45-20,000 Hz

SPE-284/WS

Power rating (RMS)	50 W
Peak music power output (MAX)	100 W
Sensitivity	89 dB/W/m
Mounting cutout	Ø 220 mm
Mounting depth	85 mm
Dimensions	Ø 250 mm x 96 mm
Outside diameter	Ø 250 mm
Width	Ø 250 mm
Depth	96 mm
Protective class	IP65
Admiss. ambient temp.	0-100 °C
Weight	0.95 kg
Packing unit	2
Type of speaker	200
Packing dimensions (W x H x L)	0.26 x 0.225 x 0.265 m
Gross weight	2.42 kg
Net weight	1.933 kg